

FACILITY CARE[®]

Design, Operation & Maintenance of Healthcare Facilities

facilitycare.com

A PATIENT-CENTERED ED

EMERGENCY

Volume 14 • Number 5 • August 2009

PLUS

Post-Occupancy
Evaluation

Reducing HAIs

A Journey
on the Gurney

ry/audit trail, a Request-to-Exit sensor and the capacity to accommodate up to 2,400 unique credential IDs per lock. SARGENT Manufacturing, New Haven, Conn.

For more information, call (800) 727-5477 or visit sargentlock.com.

Dehumidification



The FreeDry unit combines the benefits of cooling-based dehumidification technology with an advanced low-temperature desiccant rotor for moisture removal capacity and 60 percent lower annual operating costs. The unit uses waste heat instead of natural gas to reactivate the desiccant wheel. The heat pump and multiple-scroll air-conditioning compressors allow the unit to maintain indoor humidity levels even under extreme outdoor summer conditions. Munters Corp., Fort Myers, Fla.

For more information, call (800) 843-5360 or visit munters.us.

Technology Cart



The T6 Point-of-Care Technology Cart's keyboard, monitor and work surface are independently adjustable for maximum user comfort. The one-touch adjustable keyboard is designed for healthy typing and mousing, with height adjustability

operated via foot pedal, allowing overall changes in cart height. With its small footprint, the cart maneuvers easily in crowded corridors and in tight spaces. The unit contains more than 50 percent recycled materials and is itself 95 percent recyclable. Humanscale Healthcare, New York.

For more information, call (800) 400-0625 or visit humanscale.com.

Access Control System

Networked access control systems can be expanded with the Access 800 NE1, a Wiegand-compatible Grade 1 lock with proximity reader. With the product, mechanical door hardware can be added into an access control system without additional software.

The lockset allows complete door status monitoring, and access profiles can be changed from a PC connected to the system. The product is available with the CL33800 cylindrical lock, MI.20800 mortise lock and ED5000 Series exit device. Corbin Russwin Architectural Hardware, Berlin, Conn.



For more information, call (800) 543-3658 or visit corbinrusswin.com.

Energy/Resource Monitoring



EcoView is a real-time energy and resource monitoring and control system for small commercial and residential customers. Controlled through a wireless touch panel or Web interface, the system helps users understand and track their resource consumption, allowing them to make changes and take action to cut their carbon footprints and reduce utility bills. The system can offer remote control of thermostats, e-mail updates on energy consumption, suggestions on how to reduce energy costs and much more. Advanced Telemetry LLC, San Diego.

For more information, call (858) 549-1083 or visit advancedtelemetry.com.

Air Treatment



The DryCool standard is designed to give users the ability to control temperature and humidity independently, cost-effectively treating 100 percent makeup air and working in conjunction with existing A/C systems or energy-recovering ventilators (ERV). All of the

energy required for the operation of the desiccant dehumidifier is recycled from cooling components. The unit can process between 1,000 and 16,000 cfm of makeup air. Munters Corp., Fort Myers, Fla.

For more information, call (800) 843-5360 or visit munters.us.

Green Cleaning Solutions



Clean & Green EV Traction Dry Cell Batteries are designed to save maintenance costs and reduce environmental impact when used in industrial floor cleaning equipment. The maintenance-free, valve-regulated lead acid (VRLA) construction batteries are recyclable and made from recycled products, designed for use in environmentally sensitive areas such as hospitals, airports and schools; exempt from HAZMAT shipping requirements; and compliant with OSHA regulations. Discover Energy Corp., Vancouver, British Columbia, Canada.

For more information, call (604) 730-2877 or visit discover-energy.com.

Fluorescent Lighting



The Ametrix Arrowlinear Series line of asymmetric, linear fluorescent lighting products is designed for indoor and outdoor applications, offering efficient, uniform illumination to targeted surfaces with no stray light. The fixtures are available in various mounting and configuration options, with segmented optics utilizing 95 percent specular aluminum to provide uniform distribution and wide lateral spacings. Available with an optional impact-resistant, clear acrylic lens that will not discolor over time due to heat or UV exposure, the series also has dimming options for additional energy savings. Cooper Lighting, Peachtree City, Ga.

For more information, call (770) 486-4800 or visit cooperlighting.com.